

Technical Data

Thermocouples

for use in electronics assembly industry

PA0210 – Fast responsive exposed junction

This is the standard thermocouple used throughout the reflow industry and is constructed from type K thermocouple wire. Each conductor is PTFE insulated and then twisted together to prevent tangling in use. The wire diameter is 0.2 mm (.007 in), providing a good compromise between size and strength. The thermocouple tip is pre-tinned to ease soldering to the PCB. We recommend the use of an activated flux and high temperature solder to attach this thermocouple to the PCB assembly.

Thermocouple material	Type K special limits of accuracy
Accuracy	±1.1 °C or 0.4 % of the reading (whichever is greater)
Length	800 mm (31.4 in)
Conductor diameter	0.2 mm (.007 in)
Temperature	265 °C (509 °F) maximum

PA1683 – Fine wire

This thermocouple has been developed specifically for use with BGA and ultra fine pitch surface mount components. The type K thermocouple conductors are 0.1 mm (.003 in) in diameter, each insulated with PTFE. The two conductors are then over-wrapped with a single outer PTFE sheath to prevent tangling in use. The recommended attachment method is activated flux and high temperature solder. For BGA, the accepted practice is to drill through the PCB and insert the tip until it touches a ball, and then bond the thermocouple wire in place.

Thermocouple material	Type K to British Standard Class 1
Accuracy	±1.5 °C or 0.4 % of the reading (whichever is greater)
Length	500 mm (19.6 in)
Conductor diameter	0.1 mm (.003 in)
Temperature	265 °C (509 °F) maximum

PA1571 – Ultra fine diameter, mineral insulated

The PA1571 is intended for use in high temperature applications. It is a Type K mineral insulated thermocouple with an Inconel outer sheath. The overall diameter is 0.5 mm (.01 in). It can operate to 1000 °C (1832 °F). Attachment method will depend on the application, but can include ceramic cement or mechanical fixtures.

Thermocouple material	Type K to British Standard Class 1
Accuracy	±1.5 °C or 0.4 % of the reading (whichever is greater)
Length	600 mm (23.6 in)
Conductor diameter	NA (outer sheath is 0.5 mm / .01 in)
Temperature	1,000 °C (1832 °F) maximum



PA0215 – Fiber insulated probe

Exposed junction type K thermocouple constructed from 0.2 mm (.007 in) wire with glass fiber insulation. This probe is designed for continuous use up to 355 °C (671 °F) and is therefore ideally suited to high temperature soldering applications. For best results, we recommend that the probe is attached using an activated flux and high temperature solder.

Thermocouple material	Type K special limits of accuracy
Accuracy	±1.1 °C or 0.4 % of the reading (whichever is greater)
Length	800 mm (31.4 in)
Conductor diameter	0.2 mm (.007 in)
Temperature	355 °C (671 °F) continuous 400 °C (752 °F) intermittent


PA0885 Surveyor sensor (horizontal plugs) long for use with DP5660 and Surveyor PA0883

Surveyor sensor using type K thermocouples to ANSI MC96.1 special limits of error. Dual horizontal thermocouple plugs fitted to mounting plate.

PA0886 Surveyor sensor (dual vertical plug) for use with DP5662 and DP5612 and Surveyor PA0884

Surveyor sensor using type K thermocouples to ANSI MC96.1 special limits of error. Fitted with dual vertical plug.

PA1321 Wave solder contact sensor 420 mm long to be used on CS5006, CS5012 wave soldering pallets.



Fluke Process Instruments

Americas

Salem, NH USA
Tel: +1 425 446 6780
sales@flukeprocessinstruments.com

EMEA

Cambridge, UK
Tel: +44 1223 652 400
sales@flukeprocessinstruments.co.uk

China

Beijing, China
Tel: +86 10 6438 4691
sales@flukeprocessinstruments.com.cn

Asia East and South

India Tel: +91 22 2920 7691
Singapore Tel: +65 6799 5596
sales.asia@flukeprocessinstruments.com

Worldwide Service

Fluke Process Instruments offers services, including repair and calibration. For more information, contact your local office.

www.flukeprocessinstruments.com

© 2019 Fluke Process Instruments
Specifications subject to change without notice.
7/2019 DS_Reflow_Thermocouples_EN_Rev B